

Ceconet 15 Zoll



Name	Ceconet 15 Zoll	Ceconet 15 Zoll	
Display / resolution	15,6" TFT-LCD / 1366 x 768 / opt. 1920 x 1080	15,6" TFT-LCD / 1366 x 768 / opt. 1920 x 1080	
Viewable Size	344,23mm x 193,54mm	344,23mm x 193,54mm	
Brightness	300 cd m ²	300 cd m ²	
InWall box	Cutting: 455mm x 253mm Mounting depth: 80mm	Cutting: 455mm x 253mm Mounting depth: 80mm	
Front Panel	Measures: 472mm x 277mm	Measures : 472mm x 277mm	
OSD-keyboard	Backside	/	
Touchsensor /	Projective Kapazitiv (Multiouch)	Projectiv Kapazitiv (Multiouch)	
CPU / RAM	/	Intel 4x2GHz J1900 / 4GB DDR3	Intel i5 7200U / 8GB DDR3
HDD	/	64GB SSD	128GB SSD
Front Connections	USB	1 x USB / Power Taster	
Back Connections	DVI-I, Displayport	2x USB 2.0, 2x Ethernet, VGA, RS232, HDMI	2xUSB2.0,4xUSB3.0,1xHDMI, 1xDisplayport,2xEthernet
OS	/	Windows 10 pro/Linux	
Cooling	Passive	Passive	
Speaker	Yes	Yes	
Microphone	Yes	Yes	
Options	Adapter anodised brushing (Loudspeaker integrated)	Adapter anodised brushing (Loudspeaker integrated)	
Power Supply	110 – 240 VAC / 12VDC	110 – 240 VAC / 12VDC	
Power Consumption Load / Standby	15 W / 0.5 W	26 W / 5 W	34 W / 5W
Operating temperature	0°C bis +40°C	0°C bis +40°C	
Storage temperature	-20°C bis+ 60°C	-20°C bis +60°C	
Storage humidity	Max. 80% (not condensed)	Max. 80% (not condensed)	
Weight	4,5kg	4,5kg	
RoHs compliant	Yes	Yes	
Standards	Incl. Adaptercase		
Display / resolution	CE Konform / VDE 0700/0701 EN 55024:1998 + A1:2001 + A2:2003 Teile: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, IEC 61000-4-6, EN 61000-4-11		