



Name	Edition3 TD215	Edition3 PC215	
Display / resolution	21,5" TFT-LCD / 1920 x 1080	21,5" TFT-LCD / 1920 x 1080	
Viewable Size	475,2mm x 267,3mm	475,2mm x 267,3mm	
Brightness	250 cd m ²	250 cd m ²	
Flush-mounted box	Cutting: 589mm x 324mm Depth: 80mm	Cutting: 589mm x 324mm Depth: 80mm	
Front Panel	Size: 595mm x 340mm	Size : 595mm x 340mm	
OSD-keyboard	On the back	/	
Touchsensor	Projectiv capazitve (Multiouch)	Projectiv capazitve (Multiouch)	
CPU / RAM	/	Intel Celeron J6412 / 8GB DDR4	Intel i5 1135G7 / 16 GB DDR4
HDD	/	128GB SSD	128GB SSD
Front Connections	1 x USB	1 x USB / Power Switch	
Back Connections	DVI-i and Displayport (opt.HDMI) About cable: 2x2,5mm jack plug (loudspeaker/micro) 3xUSB-A (touch/USB ext.)	2x HDMI, 2x RJ45 LAN, 4x USB3.2	2x HDMI, 2x RJ45 LAN, 4x USB3.2, 1x COM Port
OS	/	Win 10 Enterprise LTSC, Linux	
Cooling	passive	passive	
Speaker	Yes	Yes	
Microphone	Yes	Yes	
Options	Different frames	Different frames	
Power Supply	110 – 240 VAC / 12V DC	110 – 240 VAC / 12V DC	
Power Consumption Load / Standby	14W / 0.5 W	26W / 1,2 W	53W / 3W
Operating temperature	0°C to +40°C	0°C to +40°C	
Storage temperature	-20°C to 60°C	-20°C to 60°C	
Storage humidity	Max. 80% (not condensating)	Max. 80% (not condensating)	
Weight	5,7kg	5,7kg	
RoHs compliant	yes	yes	
Standards	CE Konform / VDE 0700/0701 EN 55024:1998 + A1:2001 + A2:2003 Teile: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, IEC 61000-4-6, EN 61000-4-11		