



description	Edition4 TD156	Edition4 PC156	
Display / resolution	15,6" TFT-LCD / 1920 x 1080	15,6" TFT-LCD / 1920 x 1080	
Viewable size	344,23mm x 193,54mm	344,23mm x 193,54mm	
Brightness	300 cd m ²	300 cd m ²	
Inwall box	cutout: 455mm x 253mm Depth: 80mm	Cut outt: 455mm x 253mm Depth: 80mm	
Frontplatte	dimension: 472mm x 277mm	dimension: 472mm x 277mm	
OSD-keyboard	Back side	/	
Touchsensor	Projectiv Kapazitiv (Multiouch)	Projectiv Kapazitiv (Multiouch)	
Prozessor / RAM	/	Intel Celeron J6412 / 8 GB DDR4	Intel i5 1135G7 / 16 GB DDR4
HDD	/	128GB SSD	128GB SSD
Connections front	/	Power button	
Connections back	DVI-I and Displayport (opt.HDMI) About cable:2x3,5mm jack plug (Loadspeaker/Micro), 3xUSB-A(Touch/USB- ext./power supply/audio amplifire) 1xDC hollow plug (12V for Box-PC)	2x HDMI, 2x RJ45 LAN, 4x USB3.2	2x HDMI, 2x RJ45 LAN, 4x USB3.2, 1x COM Port
OS	/	Win10 Enterprise LTSC, Linux	
cooling	Passiv	Passiv	
loadspeaker	yes	yes	
microphone	yes	yes	
Options	Frame in black or white	Frame in black or white	
Power supply	110 – 240 VAC / 12VDC	110 – 240 VAC / 12VDC	
Leistungsaufnahme Load/ Standby	15 W / 0.5 W	26 W / 5 W	34 W / 5W
Operating temperature	0°C bis +40°C	0°C bis +40°C	
Storage temperature	-20°C bis+ 60°C	-20°C bis +60°C	
Humidity	Max. 80% (not condensating)	Max. 80% (not condensating)	
weight	4,5kg	4,5kg	
RoHs-compliant	Ja	Ja	
Standards	CE Konform / VDE 0700/0701 EN 55024:1998 + A1:2001 + A2:2003 Teile: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, IEC 61000-4-6, EN 61000-4-11		